

Model No. DS 0716

LED type	Lamp
Pitch (HxV)	2.0mm x 2.0mm
Display Area	
In Cylindrical(DxH)	Φ 0.70M x 1.54M / 2.3ft x 5.04ft
Total Area	3.36 m ² / 36.09 ft ²
Screen Size (HxV) x Screens	1.09M x 1.54M x2 / 3.58ft x 5.04ft x2
Resolution (HxV) x Pictures	1092 x 768 x1 (Full Wrap) 546 x 768 x2

Luminance	> 5000 cd/m ²
Luminous Uniformity	+3.0%
Brightness Control Level	4
Color Depth	16.7 million
Contrast	> 5000 : 1

Physical Dimension (DxH) Φ 0.82M x 2.80M / 2.69ft x 9.18ft

Physical Weight	580kg / 1279 lbs
Ceiling Mount model available	None
Stand Option	None
Light Box Option	None
Light Box (Poster Size WxHxPcs)	None
Operation Temperature	-20°C ~ +40°C
Storage Temperature	-20°C ~ +85°C

Refresh Rate	90Hz
Rotational Speed	450 RPM
Power Requirement(Peak)	AC200~240V 40A, Single Phase

Power Consumption(Typical)	4000 Watt
Video Interface	DVI(1280 x 1024@60Hz)
Media Integration	IPC (Composite, S-Video included)
IPC Type	Built-in IPC
Built-in Speaker	2 Channels(w/ Amp. 10Watt)
Built-in Optics Fiber Rx	Option
Optional Image Scaler Type	Built-in ISC

